

Our Thermo Scientific Model 1535 Monitor/Alarm System is a complete temperature and performance monitoring and reporting system that tracks the "health" of your lab equipment for added protection of your valuable samples.

Thermo Scientific Model 1535 Monitor/Alarm System

Complete laboratory equipment monitoring and reporting system



The Thermo Scientific Model 1535 Monitor/Alarm System and optional converter modules allow you to define a system that meets your specific needs.



For a turnkey system, you can add an Uninterruptible Power Supply (UPS) and a Sensaphone Telephone Dialing System to your Thermo Scientific Model 1535 Monitor/Alarm System

The Thermo Scientific Model 1535 Monitor/Alarm System interfaces with as many as 24 products, or channels, to monitor equipment conditions up to 2,000 ft. (609.6 m) away. Each channel processes information from an optional converter module installed on the equipment being monitored, namely ultra-low temperature freezers, laboratory refrigerators and freezers, cryopreservation storage systems and incubators.

Programmable to suit your specific needs

Our Model 1535 Monitor/Alarm System's Thermo Scientific Enviro-Scan Microprocessor touchpad and menu system guide you through programming steps, and allow you to change parameters and create permanent records.

- Equipment conditions are continuously monitored, updated, and displayed on the 2-line, 40-character readout.
- Printing intervals are programmable, and a printout is generated automatically if an alarm condition occurs.

- Audible/visual alarms alert you to deviations in equipment status for added confidence and peace of mind. Optional Sensaphone® will call a designee.

Versatile and convenient to set up

- Personal access code for the setup and programming functions provide added security.
- Built-in dot matrix printer is a convenient source of information (e.g., date, time, unit, status).
- Standard RS-232 interface provides an easy link to an external printer.

Protection for your investment

The Thermo Scientific Model 1535 Monitor/Alarm System ensures that your valuable samples are safe and secure. When combined with a UPS and Sensaphone you or a co-worker can receive a phone call should an alarm condition occur. That's total peace of mind!

Thermo Scientific Model 1535 Monitor/Alarm System

Specification	Benefit	
Communications – Monitoring		
Format	ASCII using an RS-485 link	Continuous monitoring of equipment performance and documentary notification of any deviation
Capacity	Up to 6 data inputs from 24 channels, scan rate of 2 channels/sec.	
Distance	Up to 2,000 ft. (609.6 m), total wire	
Memory	Microprocessor retains all programming in non-volatile memory	
Display	2 line, 40 character alpha-numeric LCD	
Communications – Status		
	Standard RS-232 interface for data storage to printer and remote alarm contacts for Sensaphone or alarm monitor	Allows connection to a printer, Sensaphone®, or alarm
Alarms		
	Programmable hi/low temp, CO ₂ , O ₂ , RH, contact closure	Audible/visual notification of alarm condition
Printing		
Interval	1 min. to 24 hrs. in specified increments	Permanent record; easy-to-read, detailed log
Printer	Dot matrix, red and black permanent ink	
Recorded data	Date, time, channel number, status, designator, alarm conditions	
Electrical*		
Model 1535	90-125V, 50/60 Hz, 0.7 FLA or 180-250V, 50/60 Hz, 0.35 FLA	Can be used worldwide
Modules	Maximum 26 V DC, fused in the Model 1535	
Cord Set and Plug	8 ft. (2.4 m) with IEC 320 female plug (cabinet interconnect and country-specified plug)	
Exterior Dimensions H x W x F-B**		
Model 1535	14.0" x 6.0" x 13.8" (35.6 x 15.2 x 35.1 cm)	Compact size saves lab space
Modules	4.1" x 1.5" x 6.5" (10.4 x 3.8 x 16.5 cm)	
Ambient Conditions		
Temperature	41°F to 104°F (5°C to 40°C)	Functional in a wide range of ambient conditions
Humidity	10% to 80% up to 87.8°F (31°C), then decreasing linearly to 50% at 104°F (40°C), non-condensing	
Warranty (Model 1535)		
	1 year parts and labor	Minimizes operation cost, provides peace of mind
Weight		
Model 1535 (net/shipped)	20 lbs. (9.1 kg) / 29 lbs. (13.2 kg)	Compact design conserves space
Modules	1 lb. (0.5 kg) / 4 lbs. (1.8 kg)	

* Power/communication cables meet all Class 2 specifications (type NEC CL2) for low voltage direct current and are flame retardant. Maximum data line voltage is 26 V, and the current is limited to 1 Amp.

** F-B is the dimension from the front of the unit to the back of the unit.



Accessories (customer installed unless specified otherwise)

Cat. No.	Description
Converter Modules	
190456	Converts RTD temp probe (cryogenic) to RS-485, includes RTD probe with a 6 ft. (1.8 m) lead and one set of dry contacts, temp range -328°F to -130°F (-200°C to -90°C)
190457	Converts RTD temp probe to RS-485, includes RTD probe with a 6 ft. (1.8 m) lead and one set of dry contacts, temp range -130°F to 158°F (-90°C to 70°C)
190458	Converts RS-232 (Thermo Scientific products only) to RS-485, monitors one RS-232 port and one set of dry contacts
190459	Converts analog to RS-485, monitors four analog signals (0-1V) and two sets of dry contacts
Sensaphone Telephone Dialing System	
400047	Interfaces with standard touch-tone phone, dial specified numbers until call is received and acknowledged. Accommodates up to four input channels
400134	Interfaces with standard touch-tone phone, dial specified numbers until call is received and acknowledged. Accommodates up to eight input channels
Remote Alarms	
400011 (400040)	Remote Alarm; audible signal; 115V, 60 Hz (Remote Alarm; audible/visual signal; 115V, 60 Hz)
Other Accessories	
270078	Uninterruptible power supply; 120V, 60 Hz; runs approximately one hour with a full load
430222	Four-wire cable for power and signal transmission, consists of two 18 gauge and two 22 gauge wires on one ft. (0.3 m) increments
190470	Wall mounting bracket for Model 1535
210012	Self-stripping electrical connector
197019	Dot matrix printer paper (10 rolls)

© 2009 Thermo Fisher Scientific Inc. All rights reserved. Sensaphone is a registered trademark of Phonetics Incorporated. All other trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

North America: USA/Canada +1 866 984 3766 (866-9-THERMO)

www.thermo.com/cold

Europe: Austria +43 1 801 40 0, Belgium +32 2 482 30 30, France +33 2 2803 2180, Germany national toll free 08001-536 376, Germany international +49 6184 90 6940, Italy +39 02 02 95059 434-254-375, Netherlands +31 76 571 4440, Nordic/Baltic countries +358 9 329 100, Russia/CIS +7 (812) 703 42 15, Spain/Portugal +34 93 223 09 18, Switzerland +41 44 454 12 12, UK/Ireland +44 870 609 9203

Asia: China +86 21 6865 4588 or +86 10 8419 3588, India toll free 1800 22 8374, India +91 22 6716 2200, Japan +81 45 453 9220,

Other Asian countries +852 2885 4613 **Countries not listed:** +49 6184 90 6940 or +33 2 2803 2180

DSCS1535MTR0209

Thermo
SCIENTIFIC